

CABLIX provide a High Quality and Low cost Pig Tail with a Competitive Price, all Pig Tails are produced with low Insertion Loss & PDL. For your Tranquility and Safety Every products are Factory-terminated and Tested All connector used to assembled are made with a Ceramic Ferrules.



Specification

Parameters	Standard Fiber Cable Assemblies	
Fiber Type	SM G.652	MM(OM1/OM2/OM3)
Jacket Materials	PVC	
Connector Type	SC/LC	
Ferrule Materials	Ceramic	
Testing Wavelengths	1310±30/1550±30nm850±30/1300±30nm	
Insertion Loss(dB)	≤ 0.3dB	≤ 0.3dB
TIA/EIA-455-107	(PC/UPC/APC)	(PC/UPC)
Return Loss(dB)	≥45dB(PC/UPC)	≥35dB(PC/UPC)
TIA/EIA-455-107	≥55dB(APC)	≥35dB(PC/UPC)
Exchangeability	≤ 0.2dB	
Operating Temperature (° C)	-10~ + 70	
Storage Temperature (° C)	-40 ~ +85	
Package	1unit/bag	

SIMPLEX - APC

OT9-06 15A PigTail Fiber 09/125 SC/APC Simplex 1.5M/0,9 mm

OT9-11 15A PigTail Fiber 09/125 LC/APC Simplex 1.5M/0,9 mm

SIMPLEX – UPC

OT9-06 15U PigTail Fiber 09/125 SC/UPC Simplex 1.5M/0,9 mm

OT9-11 15U PigTail Fiber 09/125 LC/UPC Simplex 1.5M/0,9 mm

OT5-06 15U PigTail Fiber 50/125 SC/UPC Simplex 1.5M/0,9 mm

OT5-11 15U PigTail Fiber 50/125 LC/UPC Simplex 1.5M/0,9 mm

XX=06 Connector SC

XX=11 Connector LC

15= 1.5 Mts

Ask for other length

Z=A- APC

Z=U- UPC



STREET



HOSPITAL



INDUSTRIES



FTTH



OTHERS