

16 Core Fiber Optic Distribution Box

Description

This box is used as a termination point for the feeder cable to connect with drop cable in FTTX communication network system.

It integrates fiber splicing, splitting, distribution, storage and cable connection in one unit. Meanwhile, it provides solid protection and management for the FTTX network building.

Features

- 1、Total enclosed structure.
- 2、Material: GG" >= wet-proof、 water-proof、 dust g i f f] Xek\$ aging, protection level up to IP6/%
- 3、Clamping for feeder cable and drop cable, fiber splicing, fixation, storage distribution ... etc all in one.
- 4、Cable, pigtails, patch cords are running through own path without disturbing each other, cassette type SC adaptor .installation, easy maintenance.
- 5、Distribution panel can be flipped up, feeder cable can be placed in a cup-joint way, easy for maintenance and installation.
- 6、Box can be installed by the way of wall-mounted or poled-mounted,suitable for both indoor and outdoor uses.



: f e j ^ I i X k f e

D X k i ^ X c	J ^ q	D X o : X g X Z ^ k p	Nos of PLC	E f j f] 8 [X g k f i	N \ ^ _ k	G f i k j
Strengthen Polymer Plastic	A*B*C(mm) 385*240*128	Splice 96 Fibers (4trays, 24 fiber/tray)	PLC Splitter 2 pcs of 1x8 1 pcs of 1x16	24 pcs of SC(max)	3.8kg	4 in 16 out

Standard Accessories

- Cleaning kit : 1pcs
- Metal spanner: 2pcs
- Mastic sealant: 1pcs
- Insulating tape : 1pcs
- Metal ring :9pcs
- Plastic ring : 4pcs
- Plastic plug : 21pcs
- Fiber protective tube: 2pcs
- Expansion screw: 2pcs
- Cable tie:3mm*10mm 10pcs
- Heat-shrink sleeve:1.2mm*60mm (- pcs



Packing List

G: J & 8I KFE	Gross Weight (Kg)	Net Weight, B^ -	Carton Size (cm)	: Yd , d ‡-
4	16	15	50*42*31	0.065

Installation instruction

